

btable


Enrico Schumann
es@enricoschumann.net

1 btable

btable creates a simple barplot in a \LaTeX tabular. As an example, add this to a Sweave file:

```
\begin{tabular}{ll}  
<<echo=false, results=tex>>=  
x <- 1:5  
cat(btable(x, before = paste(x, "&"), after= "\\\\\\n"))  
@  
\end{tabular}
```

The output should be:



2 dctable

```
> x <- array(1:6, dim = c(3, 2))
```

```
---  
---  
---
```

```
> toLatex(sessionInfo())
```

- R version 4.1.1 (2021-08-10), x86_64-pc-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=de_CH.UTF-8, LC_COLLATE=C, LC_MONETARY=de_CH.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=de_CH.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=de_CH.UTF-8, LC_IDENTIFICATION=C
- Running under: Ubuntu 21.04
- Matrix products: default
- BLAS: /usr/lib/x86_64-linux-gnu/openblas-openmp/libblas.so.3
- LAPACK:
/usr/lib/x86_64-linux-gnu/openblas-openmp/libopenblas-p0.3.13.so
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: textutils 0.2-1
- Loaded via a namespace (and not attached): compiler 4.1.1, tools 4.1.1